

**SPE 167552****An Improved Predictive Tool for Liquid Loading in a Gas Well**¹Fadairo Adesina SPE, ¹Femi-Oyewole Damilola SPE and ²Falode Olugbenga, SPE
¹Covenant University Ota, Nigeria, ²University of Ibadan, Nigeria

Copyright 2013, Society of Petroleum Engineers

This paper was prepared for presentation at the Nigeria Annual International Conference and Exhibition held in Lagos, Nigeria, 30 July–1 August 2013.

This paper was selected for presentation by an SPE program committee following review of information contained in an abstract submitted by the author(s). Contents of the paper have not been reviewed by the Society of Petroleum Engineers and are subject to correction by the author(s). The material does not necessarily reflect any position of the Society of Petroleum Engineers, its officers, or members. Electronic reproduction, distribution, or storage of any part of this paper without the written consent of the Society of Petroleum Engineers is prohibited. Permission to reproduce in print is restricted to an abstract of not more than 300 words; illustrations may not be copied. The abstract must contain conspicuous acknowledgment of SPE copyright.

Abstract

As the search for natural gas becomes increasingly high due to its high demand worldwide, the oil and gas industry is faced with the challenge of liquid loading in gas or condensate wells. It is imperative to properly design and predict the operational parameters necessary for handling flow assurance challenges due to simultaneous flow of gas with liquid. The model of Guo et al is the most recent systematic approach for predicting liquid loading in gas well. However, it did not account for the accumulation and kinetic terms in the momentum energy equation used to estimate bottom-hole pressure in a gas/oil/water/solid four phase flowing well. The two neglected terms in Guo et al formulation have significant effects on the gas well operational parameters such as the minimum gas flow rate for preventing liquid loading.

This paper presents an improved model that describes a systematic approach for estimating liquid loading in a gas well without neglecting any term in the fundamental momentum equation. The results obtained showed that at the early production time where initial transience at the onset of flow is experienced, the critical gas flow rate obtained from the new model is lower than that predicted from Guo et al model due to inclusion of accumulation term while at the later production time, the critical gas flow rate obtained becomes higher than that predicted from Guo et al model and increases as the transient period elapses. Results further show that at some point during production, the minimum energy required to lift liquids out of the wellbore is more than that required at the earlier stage of production. The new model is reasonable, reliable and better when compare with Turner et al and Guo et al models. It is useful for operators to refine their procedures and better manage the risk of liquid loading during natural gas production.

Introduction

Liquid loading is refers to as the inability of a gas well to remove liquids which are produced along with gas from a wellbore. This phenomenon is activated when the produced gas has lost its capacity to carry up the co-produced fluids up the wellbore (Coleman et al, 1999). A typical gas well produces natural gas and most often it carries either liquid or condensate in the form of mist. The associated liquids accumulate in the production well; hence a